

3/5/1

DIALOG(R)File 351:Derwent WPI

(c) 2002 Derwent Info Ltd. All rts. reserv.

013035224 \*\*Image available\*\*

WPI Acc No: 2000-207075/ 200019

XRPX Acc No: N00-154174

Rapid mixing injection valve for internal combustion engine - has electrostrictive or magnetostrictive piezo-actuator with valve needle, hydraulic chamber and separating elements

Patent Assignee: SIEMENS AG (SIEI )

Inventor: GOTTLIEB B; KAPPEL A; MEIXNER H; MOCK R

Number of Countries: 002 Number of Patents: 002

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
DE 19838862	A1	20000309	DE 1038862	A	19980826	200019 B
FR 2782796	A1	20000303	FR 9910730	A	19990824	200019

Priority Applications (No Type Date): DE 1038862 A 19980826

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

DE 19838862 A1 13 G01F-013/00

FR 2782796 A1 G01F-013/00

Abstract (Basic): DE 19838862 A

The valve comprises a housing (2) provided with a piezo-actuator (1) and a hydraulic chamber (8) bounded by primary (4,41) and secondary (6,61) separating elements. There is a fluid chamber (7) with a valve needle (5) and reservoir (10), filled with hydraulic fluid (14), and a flexible outer wall connected to the needle.

The throttled-down connecting tube (9,91) connects the reservoir to the hydraulic chamber.

ADVANTAGE - Gives highly precise mixture. Improves use of fuel and reduces emissions.

Dwg.1/7

Title Terms: RAPID; MIX; INJECTION; VALVE; INTERNAL; COMBUST; ENGINE; ELECTROSTRICTIVE; MAGNETOSTRICTIVE; PIEZO; ACTUATE; VALVE; NEEDLE; HYDRAULIC; CHAMBER; SEPARATE; ELEMENT

Derwent Class: P42; Q53; Q57; S02; V06; X22

International Patent Class (Main): G01F-013/00

International Patent Class (Additional): B05B-009/047; F02M-047/06;

F02M-051/06; F15B-001/00; F15B-015/00; F16K-031/00

File Segment: EPI; EngPI